


TEMPERATURE TRANSMITTER 4/20MA

PASSIVE HT-NTC

- Transmitter with 4-20 mA 2-wire (PASSIVE) for Pt100, NTC 10K & PTC 1K sensors and wireless 2-3-4 for temperature measurement in industrial environments, with excellent EMC characteristics.
- Allows remote transmission temperature , with safety and interference immunity .
- The output is linearized with temperature, with a high load capacity loop that allows a wide range from 6V to 30V supply (protected against polarity reversal) .
- It has an intelligent adaptive filter to stabilize the signal.
- Its small size , encapsulated and sealed with resin format provides high electric strength, mechanical and environmental .
- Allows a quick and easy configuration via PC through wireless communication module based programming with USB (promptly via smartphone) . Is not necessary to connect any cable and avoid to waste time and made mistakes with wrong connections.
- It has an internal data logger that records temperature continuously for subsequent dump to your computer.
- **High accuracy by the A / D 16bit (< 0.1 ° C).**



HERTEN S.L.
 Cami Hostalassos, 11
 12550 Almazora
 Castellón
 Spain
 Telf. 964 21 11 81
 Fax. 964 20 73 90

Email: comercial@hertensl.com
www.hertensl.com




 **HIGH CAPACITY**
load 900Ω at 24VDC.
Allows a large number of receivers.

 **HIGH PRECISION**
0,1°C
16bits
Allows up to tenths of a degree.
Example 52.7 ° C.
2-3-4 probe strands.
(4-wire high precision).



 **FLOATING CLAMPS**
Includes spring-loaded screws.
Facilitates the incorporation
to DINB heads.


 **ERROR CORRECTION**
digitally sensor.
Calibration gain x
offset +/-

*Transmitter 4/20mA Passive
RTD (Pt100, Pt1000, Ni100)*



 **PROTECTED**
Fully encapsulated in epoxy resin.
Harsh, hostile environments.
Tropicalized.
Work's temperature -40/+85°C

 **WIDE RANGE**
supply 6.. 30V.
Low power consumption.

 **DATA LOGGER**
Incorporates recording temperature / time.
Review of events, failures, ..
Wireless download to Pc.

 **WIRELESS PROGRAMMING**
Quick and easy configuration via PC.
No connections. Without calibrators.
(promptly via smartphone).

HERTEN S.L.
Cami Hostalassos, 11
12550 Almazora
Castellón
Spain
Telf. 964 21 11 81
Fax. 964 20 73 90

Email: comercial@hertensl.com
www.hertensl.com



Transmitter with 4-20 mA 2-wire (PASSIVE) for Pt100, NTC 10K , PTC 1K sensors and wireless 2-3-4 for temperature measurement in industrial environments, with excellent EMC characteristics

Allows remote transmission temperature , with safety and interference immunity .

The output is linearized with temperature, with a high load capacity loop that allows a wide range from 6V to 30V supply (protected against polarity reversal) .

It has an intelligent adaptive filter to stabilize the signal.

Its small size , encapsulated and sealed with resin format provides high electric strength, mechanical and environmental .

Allows a quick and easy configuration via PC through wireless communication module based programming with USB (promptly via smartphone) .

It has an internal data logger that records temperature continuously for subsequent dump to your computer.

High accuracy by the A / D 16bit (< 0.1 ° C).

TECHNICAL CHARACTERISTICS:

INPUT	Maximum cable resistance	20Ω/per wire		
	Connection method	2-3-4 wires		
	Linearization	BS EN 60751 (IEC751)		
	TYPES OF SENSOR	NTC 10K	PTC 1K	Pt 100
	Measuring range	-50/+125°C	-50/+120°C	-200/+800°C
	Resistance range	57/202Ω	300/3460Ω	18,5/378Ω
	Technical connection	2 hilos	2 hilos	2, 3, 4 hilos

HERTEN S.L.

Cami Hostalassos, 11

12550 Almazora

Castellón

Spain

Telf. 964 21 11 81

Fax. 964 20 73 90

Email: comercial@hertensl.com

www.hertensl.com



Self-powered	by loop
Supply voltage	6.. 32VDC
Protected against polarity reversal	

POWER SUPPLY



PRECISION

Maximum transmission error	0,1% F.S.
EMI	<0,5%
Temperature coefficient	<100ppm
Overall maximum error	0,1°C



Programmable time between samples	1.. 3.600seg
Capacity	4K (4.000 valores). Non-volatile memory.
Circular Buffer. Old values are overwritten.	
Wireless download registration on Pc.	
Display / print, zoom and guide lines graphic temperature / time.	

incorporated

DATA LOGGER

Low Voltage Directive (LVD). Directive 2006/95/CE	
Electromagnetic compatibility. Directive 2004/108/CE	
CE	Emitted interference EN 61000-6-4
	Immunity to interference EN 61000-6-2
	Separate collection of electrical appliances.
Directive 2002/96/CE	

RoHS
Compliant

STANDARDS

Temperature-linear	4/20mA Passive
	or reverse 20/4mA Passive
Output's resolution (mA)	1µA
Rated load	900Ω@ 24VDC - 20mA
	1200Ω@ 30VDC - 20mA
Sensor break detection	HIGHSCALE 21,5mA
	LOWSCALE 3,8mA
Sensor error correction (gain and zero) digital	
Correction factor resolution	0,1°C
Sampling time	300mseg
Response time 10.. 90%	600mseg
Rejection's frequency	50-60Hz
Intelligent filter	Adaptative

OUTPUT




HERTEN S.L.
Cami Hostalassos, 11
12550 Almazora
Castellón
Spain
Telf. 964 21 11 81
Fax. 964 20 73 90

Email: comercial@hertensl.com
www.hertensl.com





FORMAT

Mounting on	DIN/B Head
Fastening with	2 screws floating dock
Dimensions	Ø 45 x h 23
Protection	IP55
Protected with	waterproof silicone epoxy
Electrical connection	screw terminal
Maximum conductor section	1 mm ²
Peeled length	8mm
Box material	Nylon (PA66)
Weight	30gr.



RTD

CONEXIONADO 2-3-4 HILOSCAPACIDAD
BUCLE SALIDA

HERTEN S.L.

Cami Hostalassos, 11

12550 Almazora


Castellón

Spain

Telf. 964 21 11 81

Fax. 964 20 73 90

Email: comercial@hertensl.comwww.hertensl.com



The transmitters can be configured in two ways:

a) With a data base RFID + PC program

b) With an Smartphone with NFC system and a concrete program (Only for Android)

Of this way you can configured the transmitter in the office or if you need in field of working.

REALLY EASY AND FLEXIBLE TO CONFIGURE

HERTEN S.L.
Cami Hostalassos, 11
12550 Almazora
Castellón
Spain
Telf. 964 21 11 81
Fax. 964 20 73 90

Email: comercial@hertensl.com
www.hertensl.com

